

FEATURES

- Fast switching
- Low on-resistance
- Low gate charge
- 100% Single Pulse Avalanche Energy Test




Product Summary			
V _{DS}	R _{DS(on)} (mΩ) Typ	I _D (A)	Q _g (Typ)
-100V	35@ -10V	-30	90nc

MECHANICAL DATA

- Case: TO-220\ITO-220\TO-263\TO-262\TO-251\TO-252 Package

Ordering Information

Part No.	Package Type	Package	Quantity(box)
D30P10	TO-220	Tube	1000
D30P10F	ITO-220	Tube	1000
D30P10D	TO-263	Tape & Reel	800
D30P10E	TO-262	Tube	1000
D30P10M	TO-252	Tape & Reel	3000
D30P10N	TO-251	Tube	1000



Pin Definition:

1. Gate
2. Drain
3. Source

Block Diagram




Table1 Absolute Maximum Ratings (T_C=25°C, unless otherwise specified)

Parameter	Symbol	TO-220/TO-263/TO-262 TO-251/TO-252	ITO-220	Unit
Drain-Source Voltage	V _{DS}	-100		V
Gate-Source Voltage	V _{GS}	±20		V
Continuous Drain Current	I _D	-30		A
		-21		
Pulsed Drain Current (Note 1)	I _{DM}	-120		A
Single Pulse Avalanche Energy(Note 2)	E _{AS}	317		mJ
Avalanche Current(Note 1)	I _{AR}	2		A
Power Dissipation T _C =25°C	P _D	120	48	W
Operating Junction and Storage Temperature	T _J /T _{STG}	-55 ~ +150		°C
Maximum Temperature for soldering	T _L	300		°C

D30P10 Series

Table 2. Thermal Characteristics

Parameter	Symbol	TO-220/TO-263/TO-262 TO-251/TO-252	ITO-220	Unit
Thermal resistance Junction to Ambient	$R_{\theta JA}$	62	62	$^{\circ}\text{C/W}$
Thermal resistance Junction to Case	$R_{\theta JC}$	1.04	2.6	$^{\circ}\text{C/W}$

Table 3. Electrical Characteristics ($T_J=25^{\circ}\text{C}$, unless otherwise specified)

Parameter		Symbol	Test Conditions	Min	Typ	Max	Unit
Off Characteristics							
Drain-Source Breakdown Voltage		BV _{DSS}	V _{GS} =0V,I _D =-250μA	-100	--	--	V
Drain-Source Leakage Current		I _{DSS}	V _{DS} =-100V,V _{GS} =0V	--	--	-1	μA
Gate- Source Leakage Current	Forward	I _{GSS}	V _{GS} =20V,V _{DS} =0V	--	--	100	nA
	Reverse		V _{GS} =-20V,V _{DS} =0V	--	--	-100	nA
On Characteristics(Note 4)							
Gate Threshold Voltage		V _{GS(TH)}	V _{DS} =V _{GS} ,I _D =-250μA	-1	--	-3	V
Static Drain-Source On-State Resistance		R _{DS(ON)}	V _{GS} =-10V,I _D =-15A	--	35	51	mΩ
Dynamic Characteristics(Note 5)							
Input Capacitance		C _{ISS}	V _{DS} =-25V,V _{GS} =0V,f=1MHz	--	2700	--	pF
Output Capacitance		C _{OSS}		--	790	--	pF
Reverse Transfer Capacitance		C _{RSS}		--	450	--	pF
Switching Characteristics (Note 5)							
Turn-On Delay Time		t _{d (on)}	V _{DD} =-50V,I _D =-15A,V _{GS} =-10V R _G =9.1Ω	--	17	--	ns
Turn-On Rise Time		t _r		--	80	--	ns
Turn-Off Delay Time		t _{d (off)}		--	45	--	ns
Turn-Off Fall Time		t _f		--	65	--	ns
Total Gate Charge		Q _G	V _{DD} =-50V,I _D =-15A, V _{GS} =-10V	--	90	--	nC
Gate-Source Charge		Q _{GS}		--	15	--	nC
Gate-Drain Charge		Q _{GD}		--	35	--	nC
Drain-Source Diode Characteristics and Maximum Ratings							
Drain-Source Diode Forward Voltage		V _{SD}	V _{GS} =0V, I _S =-30A	--	--	-1.5	V
Maximum Continuous Drain-Source Diode Forward Current (Note 3)		I _S		--	--	-30	A
Reverse Recovery Time		t _{rr}	V _{GS} =0V, I _F =-15A	--	90	--	ns
Reverse Recovery Charge		Q _{RR}	dI _F /dt=100A/μs (Note 1)	--	70	--	nC

Notes : 1 Repetitive Rating: Pulse width limited by maximum junction temperature

2 $L=0.5\text{mH}$ $I_D=-35.6A, V_{DD}=-50V, V_{GATE}=-100V$, Starting $T_J=25^{\circ}\text{C}$

3 Surface mounted on FR4 Board, $t \leq 10\text{sec}$

4 Pulse Test: Pulse width $\leq 300\mu s$, Duty cycle $\leq 2\%$

5 Guaranteed by design, not subject to production

Typical characteristics Diagrams




Figure 1 Output Characteristics




Figure 4 $R_{DS(on)}$ -Junction Temperature




Figure 2 Transfer Characteristics




Figure 5 Gate Charge




Figure 3 $R_{DS(on)}$ - Drain Current




Figure 6 Source- Drain Diode Forward

Typical characteristics Diagrams




Figure 7 Capacitance vs Vds




Figure 9 Drain Current vs Case Temperature




Figure 8 Safe Operation Area




Figure 10 Power De-rating





Figure 11 Normalized Maximum Transient Thermal Impedance


Product Names Rules



D30P10 Series


Dimensions

TO-220 PACKAGE OUTLINE DIMENSIONS



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	MIN	MAX	MIN	MAX
A	4.25	4.87	0.167	0.192
A1	1.07	1.47	0.042	0.058
A2	2.03	2.92	0.080	0.115
b	0.51	1.11	0.020	0.044
b1	0.97	1.6	0.038	0.063
C	0.3	0.7	0.012	0.028
D	14.6	15.9	0.575	0.626
D1	8.04	9.3	0.317	0.366
E	9.57	10.57	0.377	0.416
e	2.34	2.74	0.092	0.108
L	12.58	14.3	0.495	0.563
L1	2.8	4.2	0.110	0.165
P	3.4	4.14	0.134	0.163
Q	2.45	3	0.096	0.118

ITO-220 PACKAGE OUTLINE DIMENSIONS




Symbol	Dimensions In Millimeters		Dimensions In Inches	
	MIN	MAX	MIN	MAX
A	4.24	4.9	0.167	0.193
A1	2.3	2.92	0.091	0.115
A2	2.61	2.81	0.103	0.111
b	0.3	1	0.012	0.039
b1	0.9	1.55	0.035	0.061
C	0.3	0.7	0.012	0.028
D	14.5	16.36	0.571	0.644
D1	8.8	9.41	0.346	0.370
E	9.5	10.5	0.374	0.413
e	2.3	2.75	0.091	0.108
L	12.6	14	0.496	0.551
L1	2.45	4.3	0.096	0.169
P	2.9	3.8	0.114	0.150
Q	2.5	3.55	0.098	0.140

D30P10 Series


Dimensions

TO-263 PACKAGE OUTLINE DIMENSIONS



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	MIN	MAX	MIN	MAX
A	4.25	4.87	0.167	0.192
A1	1.07	1.47	0.042	0.058
A2	0	0.25	0.000	0.010
b	0.61	1.01	0.024	0.040
b1	1.2	1.34	0.047	0.053
C	0.3	0.6	0.012	0.024
D	9.48	10.84	0.373	0.427
D1	8.49	9.3	0.334	0.366
E	9.7	10.31	0.382	0.406
e	4.88	5.28	0.192	0.208
L	4.46	5.85	0.176	0.230
L1	1.33	2.33	0.052	0.092
L2	0	2.2	0.000	0.087

TO-262 PACKAGE OUTLINE DIMENSIONS




Symbol	Dimensions In Millimeters		Dimensions In Inches	
	MIN	MAX	MIN	MAX
A	10.14	11.14	0.399	0.439
B	9.57	10.57	0.377	0.416
C	1.15	1.84	0.045	0.072
D	2.95	3.95	0.116	0.156
E	12.25	13.75	0.482	0.541
F	2.34	2.74	0.092	0.108
G	0.51	1.11	0.020	0.044
H	0.97	1.57	0.038	0.062
I	4.25	4.87	0.167	0.192
J	1.07	1.47	0.042	0.058
K	2.03	2.92	0.080	0.115
L	0.3	0.6	0.012	0.024

D30P10 Series


Dimensions

TO-251 PACKAGE OUTLINE DIMENSIONS



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	MIN	MAX	MIN	MAX
A	6.85	7.25	0.270	0.285
B	5.8	6.3	0.228	0.248
C	5	5.53	0.197	0.218
D	6.3	6.8	0.248	0.268
E	3.5	4.35	0.138	0.171
F	2.19	2.39	0.086	0.094
G	0.45	0.85	0.018	0.033
H	2.2	2.4	0.087	0.094
I	0.41	0.61	0.016	0.024
J	0.71	1.31	0.028	0.052
K	0.41	0.61	0.016	0.024

TO-252 PACKAGE OUTLINE DIMENSIONS



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	MIN	MAX	MIN	MAX
A	6.85	7.25	0.270	0.285
B	5.8	6.3	0.228	0.248
C	5	5.53	0.197	0.218
D	6.3	6.8	0.248	0.268
E	2.6	3.3	0.102	0.130
F	2.19	2.39	0.086	0.094
G	0.45	0.85	0.018	0.033
H	2.2	2.4	0.087	0.094
I	0.41	0.61	0.016	0.024
J	0	8	0	8
K	1.45	1.85	0.057	0.073
L	0.41	0.61	0.016	0.024
M	0	0.12	0.000	0.005
N	0.6	1	0.024	0.039

Friendship Reminder

■ JiNan JingHeng (hereinafter referred to as JH) reserves the right to make changes to this document and its products and specifications at anytime without notice.

■ Customers should obtain and confirm the latest product information and specifications before final design, purchase or use.

■ JH makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does JH assume any liability for application assistance or customer product design.

■ JH does not warrant or accept any liability with products which are purchased or used for any unintended or unauthorized application.

■ No license is granted by implication or otherwise under any intellectual property rights of JH.

■ JH's products are not authorized for use as critical components in life support devices or systems without express written approval of JH.