



SC1065CT SC1065D1

SILICON CARBIDE SCHOTTKY DIODE
Reverse Voltage - 650 Volts
Forward Current - 10.0Amperes

DESCRIPTION

SiC Schottky Diode has no switching loss, provides improved system efficiency against Si diodes by utilizing new semiconductor material-Silicon Carbide, enables higher operating frequency, and helps increasing power density and reduction of system size /cost. Its high reliability ensures robust operation during surge or over-voltage conditions.

FEATURES


- Max Junction Temperature 175°C
- High Surge Current Capacity
- Positive Temperature Coefficient
- Ease of Paralleling
- No Reverse Recovery/No Forward Recovery

MECHANICAL DATA

- Case: JEDEC TO-220AB/TO-263AB
- Molding compound meets UL94V-0 flammability rating
- Terminals: Lead solderable per J-STD-002 and JESD22-B102
- Polarity: As marked
- Mounting Torque: 10 in-lbs maximum


TYPICAL APPLICATIONS

- General Purpose
- SMPS, Solar inverter, UPS
- Power Switching Circuits



Dimensions in inches and (millimeters)

SC1065D1



Dimensions in inches and (millimeters)

MAXIMUM RATINGS

(Ratings at 25°C ambient temperature unless otherwise specified)

Parameter	Symbol	SC1065CT SC1065D1	Unit
Maximum repetitive peak reverse voltage	V _{RRM}	650	V
Continuous Rectified Forward Current	I _F	10	A
Repetitive Forward Surge Current (NOTE 1)	I _{F, RM}	40	A
Operating junction temperature range	T _J	-55 to +175	°C
Storage temperature range	T _{stg}	-55 to +175	°C

Notes: 1.Half-Sine Pulse, t_p=8.3ms

RATINGS AND CHARACTERISTIC OF SC1065CT SC1065D1

ELECTRICAL CHARACTERISTICS ($T_A=2^\circ\text{C}$ Unless otherwise noted)

Parameter	Test Conditions		Symbol	TYP.	MAX.	Unit
Instantaneous forward voltage	$I_F=10\text{A}$	$T_A=25^\circ\text{C}$	V_F	1. 30	1. 6	V
		$T_A=175^\circ\text{C}$		1. 50	1. 8	
Reverse current	$V_R=650\text{V}$	$T_A=25^\circ\text{C}$	I_R	–	10	μA
		$T_A=125^\circ\text{C}$		–	40	
		$T_A=175^\circ\text{C}$		–	100	
Typical junction capacitance	$V_R=1\text{V}, f=100\text{kHz}$		C_j	650	–	pF
	$V_R=4\text{V}, f=100\text{kHz}$			450	–	
	$V_R=40\text{V}, f=100\text{kHz}$			160	–	

THERMAL CHARACTERISTICS ($T_A=25^\circ\text{C}$ Unless otherwise noted)

Parameter	Symbol	SC1065CT SC1065D1	Unit
Typical thermal resistance ²⁾	$R_{\theta JC}$	2.5	$^\circ\text{C}/\text{W}$

2.Thermal resistance from junction to case

RATINGS AND CHARACTERISTIC OF SC1065CT SC1065D1

FIG.1-FORWARD CURRENT DERATING CURVE




FIG.2-FORWARD CURRENT DERATING CURVE




FIG.3-TYPICAL JUNCTION CAPACITANCE




FIG.4-REVERSE CHARACTERISTICS

