

DESCRIPTION

SiC Schottky Diode has no switching loss, provides improved system efficiency against Si diodes by utilizing new semiconductor material-Silicon Carbide, enables higher operating frequency, and helps increasing power density and reduction of system size /cost. Its high reliability ensures robust operation during surge or over_voltage conditions.

FEATURES

- Max Junction Temperature 175°C
- High Surge Current Capacity
- Positive Temperature Coefficient
- Ease of Paralleling
- No Reverse Recovery/No Forward Recovery

MECHANICAL DATA

- Case: JEDEC TO-247AC
- Molding compound meets UL94V-0 flammability rating
- Terminals: Lead solderable per J-STD-002 and JESD22-B102
- Polarity: As marked
- Mounting Torque: 10 in-lbs maximum

TYPICAL APPLICATIONS

- General Purpose
- SMPS, Solar inverter, UPS
- Power Switching Circuits


KEY PERFORMANCE AND PACKAGE PARAMETERS

Type	V _{DC}	I _F	Q _c	T _J ,max	Package
SC25170P	1700V	25A	300nC	175°C	TO-247AC

TO-247AC



Base common cathode



MAXIMUM RATINGS

(Ratings at 25°C ambient temperature unless otherwise specified)

Parameters	Symbol	Value	Unit
Maximum repetitive peak reverse voltage	V_{RRM}	1700	V
Continuous forward current for $R_{th(j-c)}$	I_F	25($T_c=150^{\circ}C$) 45($T_c=125^{\circ}C$) 75($T_c=25^{\circ}C$)	A
Non-repetitive forward surge current (Half-Sine Pulse, $t_p=8.3ms$)	I_{FSM}	180 ($T_c=25^{\circ}C$)	A
I^2t value	I^2t	134($T_c=25^{\circ}C$)	A^2S
Power dissipation for $R_{th(j-c,max)}$ ($T_c=25^{\circ}C$)	P_{tot}	375	W
Operating junction temperature range	T_j	-55...175	$^{\circ}C$
Storage temperature range	T_{stg}	-55...175	$^{\circ}C$

THERMAL CHARACTERISTICS

Parameter	Symbol	Value		Unit
		Typ	Max	
Diode thermal resistance junction-case	$R_{th(j-c)}$	-	0.40	$^{\circ}C/W$

ELECTRICAL CHARACTERISTICS (T_j=25°C Unless otherwise noted)

Parameter	Symbol	Conditions	Value			Unit
			min	typ	max	
DC blocking voltage	V _{DC}	T _j =25...175°C	1700	-	-	V
Diode forward voltage	V _F	I _F =25A T _j =25°C	-	1.50	1.65	V
		I _F =25A T _j =125°C	-	2.00	-	
		I _F =25A T _j =175°C	-	2.25	2.80	
Reverse current	I _R	V _R =1700V T _j =25°C	-	-	100	uA
		V _R =1700V T _j =125°C	-	-	300	
		V _R =1700V T _j =175°C	-	-	1000	

DYNAMIC CHARACTERISTICS(at T_j=25°C,unless otherwise specified)

Parameter	Symbol	conditions	Value			Unit
			min	typ	max	
Total capacitive charge	Q _C	V _R =1700V		300		nC
Total capacitance	C	V _R =0V,f=1MHz		3300		pF
		V _R =800V,f=1MHz		135		
		V _R =1700V,f=1MHz		130		

FIG.1-FORWARD CURRENT DERATING CURVE




FIG.2-TYPICAL JUNCTION CAPACITANCE




FIG.3-FORWARD CURRENT DERATING CURVE






FIG.4-REVERSE CHARACTERISTICS



TO-247AC



Symbol	millimeter		
	Min	Typ	MAX
A	4.70		5.30
A1	2.21		2.59
A2	1.50		2.49
D	20.50		21.30
E	15.48		16.24
E2	4.30		5.50
e		10.92	
L	19.80		20.30
L1	4.10		4.50
ΦP		3.50	
Q	5.38		6.19
S		6.14	
b	0.99		1.40
b2	1.65		2.39
c	0.38		0.89
D1	13.07		1.35
D2	0.51		
E1	13.30		
ΦP1		7.20	

Friendship Reminder

- JiNan JingHeng(hereinafter referred to as JH)reserves the right to make changes to this document and its products and specifications at anytime without notice.
- Customers should obtain and confirm the latest product information and specifications before final design, purchase or use.
- JH makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does JH assume any liability for application assistance or customer product design.
- JH does not warrant or accept any liability with products which are purchased or used for any unintended or unauthorized application.
- No license is granted by implication or otherwise under any intellectual property rights of JH.
- JH's products are not authorized for use as critical components in life support devices or systems without express written approval of JH.