


### FEATURES

- Plastic package has Underwriters Laboratory Flammability Classification 94V-0
- Fast switching for high efficiency
- Low forward voltage drop
- Single rectifier construction
- High surge capability
- For use in low voltage ,high frequency inverters, free wheeling ,and polarity protection applications
- High temperature soldering guaranteed:260°C/10 seconds, 0.25"(6.35mm)from case
- Component in accordance to RoHS 2015/863/EU



### ITO-220AB



### MECHANICAL DATA

- Case: JEDEC ITO-220AB molded plastic body
- Terminals: Lead solderable per MIL-STD-750,method 2026
- Polarity: As marked
- Mounting Position: Any

Dimensions in inches and (millimeters)

### MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

(Ratings at 25°C ambient temperature unless otherwise specified ,Single phase ,half wave ,resistive or inductive load. For capacitive load,derate by 20%.)

Parameter		Symbols	MURF 3020CT	MURF 3040CT	MURF 3060CT	Units
Maximum repetitive peak reverse voltage		VRRM	200	400	600	Volts
Maximum RMS voltage		VRMS	140	280	420	Volts
Maximum DC blocking voltage		VDC	200	400	600	Volts
Maximum average forward rectified current(see Fig.1)	Per leg	I(AV)	15.0 30.0			Amps
	Total device					
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load (JEDEC method)		IFSM	220			Amps
Maximum instantaneous forward voltage at 15.0 A per leg(Note 1 )		VF	1.05	1.30	1.7	Volts
Maximum instantaneous reverse current at rated DC blocking voltage(Note 1)	TJ=25°C	IR	5			μA
	TJ=125°C		250			
Maximum Reverse Recovery Time (Note 2)		Trr	35			ns
Typical thermal resistance (Note 3)		RθJC	3.5			°C/W
Operating junction temperature range		TJ	-55 to+150			°C
Storage temperature range		TSTG	-55 to+150			°C

Notes: 1. Pulse test: 300us pulse width,1% duty cycle  
 2. Reverse recovery test conditions  $I_F=0.5A, I_R=1.0A, I_{rr}=0.25A$   
 3. Thermal resistance from junction to case, Per diode

FIG.1-FORWARD CURRENT DERATING CURVE




FIG.2-MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG.3-TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS





FIG.4-TYPICAL REVERSE CHARACTERISTICS



## Friendship Reminder

- JiNan JingHeng (hereinafter referred to as JH) reserves the right to make changes to this document and its products and specifications at anytime without notice.
- Customers should obtain and confirm the latest product information and specifications before final design, purchase or use.
- JH makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does JH assume any liability for application assistance or customer product design.
- JH does not warrant or accept any liability with products which are purchased or used for any unintended or unauthorized application.
- No license is granted by implication or otherwise under any intellectual property rights of JH.
- JH's products are not authorized for use as critical components in life support devices or systems without express written approval of JH.