

### FEATURES

- Plastic package has Underwriters Laboratory Flammability Classification 94V-0
- Metal silicon junction ,majority carrier conduction
- Guard ring for overvoltage protection
- Low power loss ,high efficiency
- High current capability ,low forward voltage drop
- High surge capability
- High temperature soldering guaranteed:260°C/10 seconds at terminals
- Component in accordance to RoHS 2015/863/EU




### MECHANICAL DATA

Case: SMB(DO-214AA) molded plastic body


Terminals: Solder Plated, solderable per MIL-STD-750,method 2026

Polarity: Color band denotes cathode end

#### SMB(DO-214AA)



#### Suggested PAD Layout



Dimensions in inches and (millimeters)

### TYPICAL APPLICATIONS

For use in low voltage ,high frequency inverters ,DC/DC converters, free wheeling ,and polarity protection applications

### MAXIMUM RATINGS

(Ratings at 25°C ambient temperature unless otherwise specified )

Parameter	Symbol	Value	Unit
Maximum repetitive peak reverse voltage	$V_{RRM}$	200	V
Maximum average forward rectified current (see fig.1)	$I_F(AV)$	5.0	A
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load (JEDEC method )	$I_{FSM}$	120	A
Operating junction temperature range	$T_J$	-55 to +150	°C
Storage temperature range	$T_{stg}$	-55 to +150	°C

## RATINGS AND CHARACTERISTICS OF SS520LB

### ELECTRICAL CHARACTERISTICS (T<sub>A</sub>=25°C Unless otherwise noted)

Parameter	Test Conditions		Symbol	TYP.	MAX.	Unit
Instantaneous forward voltage	I <sub>F</sub> =5.0A	T <sub>A</sub> =25°C	V <sub>F</sub> <sup>1)</sup>	0.81	0.90	V
		T <sub>A</sub> =100°C		0.69	—	
		T <sub>A</sub> =125°C		0.66	—	
	I <sub>F</sub> =2.0A	T <sub>A</sub> =25°C		0.74	—	
		T <sub>A</sub> =100°C		0.63	—	
		T <sub>A</sub> =125°C		0.59	—	
Reverse current	V <sub>R</sub> =200V	T <sub>A</sub> =25°C	I <sub>R</sub> <sup>2)</sup>	5	20	μA
		T <sub>A</sub> =100°C		—	1.0	mA
		T <sub>A</sub> =125°C		—	3.0	
Typical junction capacitance	4V, 1MHz		C <sub>J</sub>	100		pF

Notes: 1. Pulse test: 300 μs pulse width, 1% duty cycle

2. Pulse test: pulse width ≤ 40ms

### THERMAL CHARACTERISTICS

Parameter	Symbol	SMB	Unit
Typical thermal resistance <sup>3)</sup>	R <sub>θJA</sub>	70	°C/W
	R <sub>θJL</sub>	15	

3. P.C.B. mounted with 0.118" x 0.118" (3.0 mm x 3.0 mm) copper pad areas (≥ 40 μm thick)

### AVAILABLE PACK INFORMATION

Product code	Pack	Reel Size (mm)	Quantity (pcs/reel)	Box Size L×W×H (mm)	Quantity (reel/box)	Carton Size L×W×H (mm)	Quantity (box/carton)
SS520LB-SMB	T/R	Φ300	3000	340×340×40	2	370×370×370	8

# RATINGS AND CHARACTERISTICS OF SS520LB

FIG.1-FORWARD CURRENT DERATING CURVE




FIG.2-MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG.3-TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS





FIG.4-TYPICAL REVERSE CHARACTERISTICS



## Friendship Reminder

- JiNan JingHeng(hereinafter referred to as JH) reserves the right to make changes to this document and its products and specifications at anytime without notice.
- Customers should obtain and confirm the latest product information and specifications before final design, purchase or use.
- JH makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does JH assume any liability for application assistance or customer product design.
- JH does not warrant or accept any liability with products which are purchased or used for any unintended or unauthorized application.
- No license is granted by implication or otherwise under any intellectual property rights of JH.
- JH's products are not authorized for use as critical components in life support devices or systems without express written approval of JH.