

### Features

- Plastic package has Underwriters Laboratory Flammability Classification 94V-0
- Glass passivated chip junction
- High surge forward current capability
- Ideal for automated placement
- High temperature soldering guaranteed:260°C/10 seconds at terminals
- Component in accordance to RoHS 2015/863/EU



### Mechanical data

- Case:JBF molded plastic body
- Terminals:Plated leads solderable per MIL-STD-750,method 2026
- Polarity:As marked
- Mounting Position:Any

### APPLICATIONS

- Used in high frequency AC/DC bridge full wave rectification for SMPS, lighting ballaster, adapter, battery charger, home appliances, office equipment, and telecommunication applications.

JBF



HALOGEN  
FREE

### Maximum Ratings And Electrical Characteristics

(Ratings at 25°C ambient temperature unless otherwise specified ,Single phase ,half wave ,resistive or inductive load. For capacitive load,derate by 20%.)

Parameters	Symbol	RJBF401	RJBF402	RJBF404	RJBF406	RJBF408	RJBF410	Unit
Maximum repetitive peak reverse voltage	$V_{RRM}$	100	200	400	600	800	1000	V
Maximum average forward rectified current	$I_{F(AV)}$	4.0						A
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load (JEDEC method)	$I_{FSM}$	145						A
Rating for fusing( $t=8.3ms$ )	$I^2t$	87.3						A <sup>2</sup> S
Operating junction temperature range	$T_j$	-55 to 150						°C
Storage temperature range	$T_{stg}$	-55 to 150						°C

## RATINGS AND CHARACTERISTICS OF RJBF401 THRU RJBF410

### Electrical Characteristics (Per diode, $T_A=25^\circ\text{C}$ Unless otherwise noted)

Parameter	Test Conditions		Symbol	RJBF401	RJBF402	RJBF404	RJBF406	RJBF408	RJBF410	Unit
Max Instantaneous Forward Voltage	I <sub>F</sub> =4.0A		V <sub>F</sub> <sup>1)</sup>	1.25						V
Max Reverse Recovery Time	I <sub>F</sub> =0.5A,I <sub>R</sub> =1A,I <sub>RR</sub> =0.25A		trr	150			250	500		ns
Max Reverse Current	V <sub>R</sub> =V <sub>RRM</sub>	T <sub>J</sub> =25°C	I <sub>R</sub> <sup>2)</sup>	5.0						μA
		T <sub>J</sub> =100°C		70						
		T <sub>J</sub> =125°C		250						

Notes: 1.Pulse test: 300  $\mu\text{s}$  pulse width, 1% duty cycle

2.Pulse test: pulse width  $\leq 40\text{ms}$

### Thermal Characteristics

Parameter	Symbol	JBF	Unit
Typical thermal resistance <sup>3)</sup>	$R_{\theta JC}$	5.0	$^\circ\text{C/W}$

3.Thermal resistance from per diode junction to case

Fig.1-Forward Current Derating Curve




Fig.2-Maximum Non-repetitive Peak Forward Surge Current




Fig.3-Typical Instantaneous Forward Characteristics






Fig.4-Typical Reverse Characteristics




JBF



UNIT:mm		
DIM	MIN	MAX
A	4.80	5.30
B	6.20	7.00
C	7.10	8.20
D	7.90	8.90
E	2.90	3.10
F	0.04	0.08
G	0.15	0.40
H	1.30	1.50
I	0.80	1.20
J	0.70	1.60

Suggested Pad layout



Dimensions in millimeters

Dim	Min
P1	9.15
P2	7.10
Q1	1.80
Q2	2.00

## Friendship Reminder

- JiNan JingHeng (hereinafter referred to as JH) reserves the right to make changes to this document and its products and specifications at anytime without notice.
- Customers should obtain and confirm the latest product information and specifications before final design, purchase or use.
- JH makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does JH assume any liability for application assistance or customer product design.
- JH does not warrant or accept any liability with products which are purchased or used for any unintended or unauthorized application.
- No license is granted by implication or otherwise under any intellectual property rights of JH.
- JH's products are not authorized for use as critical components in life support devices or systems without express written approval of JH.