


### FEATURES

- Plastic package has Underwriters Laboratory Flammability Classification 94V-0
- Metal silicon junction ,majority carrier conduction
- Guard ring for overvoltage protection
- Low power loss ,high efficiency
- High current capability ,low forward voltage drop
- High surge capability
- High temperature soldering guaranteed:260°C/10 seconds at terminals
- Component in accordance to RoHS 2011/65/EU



### DO-15



Dimensions in inches and (millimeters)

### MECHANICAL DATA

- Case: JEDEC DO-15 molded plastic body
- Terminals: Plated axial leads, solderable per MIL-STD-750,method 2026
- Polarity: color band denotes cathode end
- Mounting Position: Any
- Weight: 0.014ounce, 0.39 gram

### TYPICAL APPLICATIONS

For use in low voltage ,high frequency inverters ,DC/DC converters, free wheeling ,and polarity protection applications

### MAXIMUM RATINGS

(Ratings at 25°C ambient temperature unless otherwise specified )

PRIMARY CHARACTERISTICS	
I <sub>F(AV)</sub>	2.0A
V <sub>RRM</sub>	60V
I <sub>FSM</sub>	50A
V <sub>F</sub> at I <sub>F</sub> =2.0A	0.43V
T <sub>JMAX</sub>	150°C

Parameter	Symbol	Value	Unit
Maximum repetitive peak reverse voltage	V <sub>RRM</sub>	60	V
Maximum average forward rectified current 0.375"(9.5mm) lead length(see fig.1)	I <sub>F(AV)</sub>	2.0	A
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load (JEDEC method at rated TL)	I <sub>FSM</sub>	50	A
Operating junction temperature range	T <sub>J</sub>	-55 to+150	°C
Storage temperature range	T <sub>stg</sub>	-55 to+150	°C

# RATINGS AND CHARACTERISTIC OF SR260SL

## ELECTRICAL CHARACTERISTICS (T<sub>A</sub>=25°C Unless otherwise noted)

Parameter	Test Conditions		Symbol	TYP.	MAX.	Unit
Instantaneous forward voltage	Per leg I <sub>F</sub> =2.0A	T <sub>A</sub> =25°C	V <sub>F</sub> <sup>1)</sup>	0.43	0.45	V
		T <sub>A</sub> =100°C		0.36	—	
		T <sub>A</sub> =125°C		0.34	—	
	Per leg I <sub>F</sub> =1.0A	T <sub>A</sub> =25°C		0.38	—	
		T <sub>A</sub> =100°C		0.30	—	
		T <sub>A</sub> =125°C		0.28	—	
Reverse current	VR=60V	T <sub>A</sub> =25°C	I <sub>R</sub> <sup>2)</sup>	60	150	μA
	VR=60V	T <sub>A</sub> =100°C		5	10	mA
	VR=60V	T <sub>A</sub> =125°C		15	30	
Typical junction capacitance	4V, 1MHz		C <sub>J</sub>	170		pF

Notes: 1.Pulse test: 300 μs pulse width,1% duty cycle

2.Pulse test: pulse width≤40ms

## THERMAL CHARACTERISTICS

Parameter	Symbol	DO-15	Unit
Typical thermal resistance <sup>3)</sup>	R <sub>θJA</sub>	35.0	°C/W
	R <sub>θJL</sub>	15.0	

3.Thermal resistance from junction to lead vertical P.C.B. mounted , 0.375"(9.5mm)lead length

## AVAILABLE PACK INFORMATION

Product code	Pack	Box Size L*W*H(mm)	Quantity (pcs/box)	Carton SizeL*W*H(mm)	Quantity (box/carton)
SR260SL-DO-15	B/P	190*80*21	500	433*203*230	50
SR260SL-DO-15	T/B	264*74*135	3000	400*267*286	10

# RATINGS AND CHARACTERISTIC OF SR260SL

FIG.1-FORWARD CURRENT DERATING CURVE




FIG.2-MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG.3-TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG.4-TYPICAL REVERSE CHARACTERISTICS




FIG.5-TYPICAL JUNCTION CAPACITANCE

