


### FEATURES

- Plastic package has Underwriters Laboratory Flammability Classification 94V-0
- Metal silicon junction ,majority carrier conduction
- Guard ring for overvoltage protection
- Low power loss ,high efficiency
- High current capability ,Low forward voltage drop
- Single rectifier construction
- High surge capability
- For use in low voltage ,high frequency inverters, free wheeling ,and polarity protection applications
- High temperature soldering guaranteed:260℃/10 seconds, 0.25"(6.35mm)from case
- Component in accordance to RoHS 2011/65/EU



**TO-263**  
**D2PAK**



### MECHANICAL DATA

- Case: JEDEC TO-263 molded plastic body
- Terminals: Solderable per MIL-STD-202,method 208
- Polarity: As marked
- Mounting Position: Any

Dimensions in inches and (millimeters)

### MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

(Ratings at 25℃ ambient temperature unless otherwise specified ,Single phase ,half wave ,resistive or inductive load. For capacitive load,derate by 20%.)

| Parameters                                                                                       |                       | Symbols          | SR 1020D2  | SR 1030D2 | SR 1040D2 | SR 1060D2 | SR 10100D2 | SR 10150D2 | SR 10200D2 | Units |
|--------------------------------------------------------------------------------------------------|-----------------------|------------------|------------|-----------|-----------|-----------|------------|------------|------------|-------|
| Maximum repetitive peak reverse voltage                                                          |                       | V <sub>RRM</sub> | 20         | 30        | 45        | 60        | 100        | 150        | 200        | Volts |
| Maximum RMS voltage                                                                              |                       | V <sub>RMS</sub> | 14         | 21        | 32        | 42        | 70         | 105        | 140        | Volts |
| Maximum DC blocking voltage                                                                      |                       | V <sub>DC</sub>  | 20         | 30        | 45        | 60        | 100        | 150        | 200        | Volts |
| Maximum average forward rectified current (see Fig.1)                                            |                       | I(AV)            | 10.0       |           |           |           |            |            |            | Amps  |
| Peak forward surge current 8.3ms single half sine-wave superimposed on rated load (JEDEC method) |                       | I <sub>FSM</sub> | 150.0      |           |           |           |            |            |            | Amps  |
| Maximum instantaneous forward voltage at 10.0 A( Note 1 )                                        |                       | V <sub>F</sub>   | 0.60       |           |           | 0.75      | 0.85       | 0.90       | 0.95       | Volts |
| Maximum instantaneous reverse current at rated DC blocking voltage(Note 1)                       | T <sub>A</sub> =25°C  | I <sub>R</sub>   | 100        |           |           |           | 30         |            |            | μ A   |
|                                                                                                  | T <sub>A</sub> =100°C |                  | 5          |           |           |           | -          |            |            | mA    |
|                                                                                                  | T <sub>A</sub> =125°C |                  | -          |           |           |           | 3          |            |            |       |
| Typical thermal resistance (Note 2)                                                              |                       | R <sub>θJC</sub> | 2.5        |           |           |           |            |            |            | °C/W  |
| Operating junction temperature range                                                             |                       | T <sub>J</sub>   | -55 to+150 |           |           |           |            |            |            | °C    |
| Storage temperature range                                                                        |                       | T <sub>STG</sub> | -55 to+150 |           |           |           |            |            |            | °C    |

**Notes:** 1.Pulse test: 300 μs pulse width,1% duty cycle

2.Thermal resistance from junction to case

# RATINGS AND CHARACTERISTIC CURVES SR1020D2 THRU SR10200D2

FIG.1-FORWARD CURRENT DERATING CURVE




FIG.2-MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG.3-TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG.4-TYPICAL REVERSE CHARACTERISTICS




FIG.5-TYPICAL JUNCTION CAPACITANCE

