


FEATURES


- Power pack
- Metal silicon junction ,majority carrier conduction
- Guard ring for overvoltage protection
- Low power loss ,high efficiency
- High current capability ,low forward voltage drop
- High forward surge capability
- High frequency operation
- Meets MSL Level 1 , per J-STD-020,LF MAX peak of 245°C (for TO-263 package)
- Solder bath temperature 275°C maximum , 10s , per JESD22-B106 (for TO-220AB and ITO-220AB package)
- Component in accordance to RoHS 2011/65/EU



TO-220AB



ITO-220AB



TO-263



MECHANICAL DATA

- Case: JEDEC TO-220AB、ITO-220AB、TO-263
- Molding compound meets UL94V-0 flammability rating
- Terminals: Lead solderable per J-STD-002 and JESD22-B102
- Polarity: As marked
- Mounting Torque: 10 in-lbs maximum

TYPICAL APPLICATIONS

For use in low voltage ,high frequency inverters ,DC/DC converters,free wheeling ,and polarity protection applications

MAXIMUM RATINGS

(Ratings at 25°C ambient temperature unless otherwise specified)

PRIMARY CHARACTERISTICS	
I _F (AV)	2×30A
V _{RRM}	200V
I _{FSM}	400A
V _F at I _F =30.0A,Per leg	0.90V
I _R	5μA
T _J (MAX)	150°C
Package	TO-220AB,ITO-220AB, TO-263
Diode variations	Common cathode

Parameter	Symbol	Value	Unit
Maximum repetitive peak reverse voltage	V _{RRM}	200	V
Maximum average forward rectified current (see fig.1)	I _F (AV)	30.0	A
Total device		60.0	
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load (JEDEC method at rated TL)	I _{FSM}	400	A
Peak repetitive reverse current per diode at t _p =2μs 1KHz	I _{RRM}	0.5	A
Operating junction and Storage temperature range	T _J ,T _{Stg}	-55 to+150	°C
Isolation voltage(ITO-220AB only)from terminals to heatsink t=1 min	V _{AC}	1500	V

RATINGS AND CHARACTERISTIC OF SR60200CT,SRF60200CT,SR60200D1

ELECTRICAL CHARACTERISTICS ($T_A=25^\circ\text{C}$ Unless otherwise noted)

Parameter	Test Conditions		Symbol	Typ.	Max.	Unit
Instantaneous forward voltage	Per leg $I_F=30.0\text{A}$	$T_A=25^\circ\text{C}$	V_F ¹⁾	0.90	0.95	V
		$T_A=100^\circ\text{C}$		0.81	-	
		$T_A=125^\circ\text{C}$		0.78	-	
		$T_A=25^\circ\text{C}$		0.69	-	
	Per leg $I_F=5.0\text{A}$	$T_A=100^\circ\text{C}$		0.59	-	
		$T_A=125^\circ\text{C}$		0.55	-	
		$T_A=25^\circ\text{C}$		5	20	μA
	$V_R=200\text{V}$	$T_A=100^\circ\text{C}$	I_R ²⁾	-	0.6	mA
		$T_A=125^\circ\text{C}$		-	2.5	
Typical junction capacitance	4V,1MHz		C_J	397		pF

Notes: 1.Pulse test: 300 μs pulse width,1% duty cycle

2.Pulse test: pulse width \leq 40ms

THERMAL CHARACTERISTICS

Parameter	Symbol	TO-220AB	ITO-220AB	TO-263	Unit
Typical thermal resistance ³⁾	$R_{\theta JC}$	1.5	2.5	1.5	$^\circ\text{C}/\text{W}$

3.Thermal resistance from junction to case

AVAILABLE PACK INFORMATION

Product code	Pack	Box Size L×W×H(mm)	Quantity(pcs/box)	Carton SizeL×W×H(mm)	Quantity(box/carton)
SR60200CT-TO-220AB	P/T	558×148×38	1000	565×225×170	5
SRF60200CT-ITO-220AB	P/T	558×148×38	1000	565×225×170	5
SR60200D1-TO-263	P/T	558×148×38	1000	565×225×170	5

RATINGS AND CHARACTERISTIC OF SR60200CT,SRF60200CT,SR60200D1

FIG.1-FORWARD CURRENT DERATING CURVE




FIG.3-TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG.5-TYPICAL JUNCTION CAPACITANCE




FIG.2-MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT






FIG.4-TYPICAL REVERSE CHARACTERISTICS




PACKAGE OUTLINE DIMENSIONS


TO-220AB




ITO-220AB



TO-263



Suggested Pad Layout



Dimensions in inches and (millimeters)