


FEATURES

- Plastic package has Underwriters Laboratory Flammability Classification 94V-0
- Metal silicon junction ,majority carrier conduction
- Guard ring for overvoltage protection
- Built-in strain relief
- For surface mounted applications
- Low profile package
- Low power loss ,high efficiency
- High current capability ,Low forward voltage drop
- High surge capability
- For use in low voltage ,high frequency inverters, free wheeling , and polarity protection applications
- High temperature soldering guaranteed:260°C/10 seconds at terminals
- Component in accordance to RoHS 2011/65/EU



SMA(DO-214AC)



MECHANICAL DATA

- Case: JEDEC SMA(DO-214AC) molded plastic body
- Terminals: Solder Plated, solderable per MIL-STD-750,method 2026
- Polarity: Color band denotes cathode end

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

(Ratings at 25°C ambient temperature unless otherwise specified ,Single phase ,half wave ,resistive or inductive load. For capacitive load,derate by 20%.)

		Symbols	SS 22	SS 23	SS 24	SS 26	SS 210	SS 215	SS 220	Units
Maximum repetitive peak reverse voltage		V _{RRM}	20	30	40	60	100	150	200	V _{olts}
Maximum RMS voltage		V _{RMS}	14	21	28	42	71	105	140	V _{olts}
Maximum DC blocking voltage		V _{DC}	20	30	40	60	100	150	200	V _{olts}
Maximum average forward rectified current		I(AV)	2.0							Amps
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load (JEDEC method)		I _{FSM}	50.0							Amps
Maximum instantaneous forward voltage at 2.0 A(Note 1)		V _F	0.55			0.70	0.85	0.90	0.95	V _{olts}
Maximum instantaneous reverse current at rated DC blocking voltage(Note 1)	T _A =25°C	I _R	100			40	20			μA
	T _A =100°C		5.0			-			mA	
	T _A =125°C		-			3.0				
Typical thermal resistance(Note 2)		R _{θJA} R _{θJL}	88.0 28.0							°C/W
Operating junction temperature range		T _J	-55 to+150							°C
Storage temperature range		T _{STG}	-55 to+150							°C

Notes: 1.Pulse test: 300 μs pulse width,1% duty cycle

2. P.C.B. mounted with 0.2 X 0.2"(5.0 X 5.0mm)copper pad areas

RATINGS AND CHARACTERISTIC CURVES SS22 THRU SS220

FIG.1-FORWARD CURRENT DERATING CURVE




FIG.2-MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG.3-TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG.4-TYPICAL REVERSE CHARACTERISTICS




FIG.5-TYPICAL JUNCTION CAPACITANCE

