

## Features

- 80Watts peak pulse power ( $t_p = 8/20\mu s$ )
- Bidirectional configurations
- Solid-state silicon-avalanche technology
- Low clamping voltage
- Low leakage current
- IEC 61000-4-2  $\pm 30kV$  contact  $\pm 30kV$  air
- IEC 61000-4-4 (EFT) 40A (5/50ns)
- IEC 61000-4-5 (Lightning) 8A (8/20 $\mu s$ )




## Applications

- Microprocessor based equipment
- Personal Digital Assistants (PDA's)
- Notebooks, Desktops, and Servers
- Portable Instrumentation
- Pagers Peripherals

## Mechanical Data

- DFN1006 package
- Molding compound flammability rating: UL 94V-0
- Packaging: Tape and Reel
- RoHS/WEEE Compliant

## Schematic & PIN Configuration



DFN1006

**Absolute Maximum Rating**


Rating	Symbol	Value	Units
Peak Pulse Power ( $t_p = 8/20\mu s$ )	$P_{PP}$	80	Watts
Peak Pulse Current ( $t_p = 8/20\mu s$ ) (note1)	$I_{pp}$	8	A
ESD per IEC 61000-4-2 (Air) ESD per IEC 61000-4-2 (Contact)	$V_{ESD}$	30 30	kV
Lead Soldering Temperature	$T_L$	260(10seconds)	°C
Junction Temperature	$T_J$	-55 to + 150	°C
Storage Temperature	$T_{stg}$	-55 to + 150	°C

**Electrical Characteristics**

Parameter	Symbol	Conditions	Min	Typical	Max	Units
Reverse Stand-Off Voltage	$V_{RWM}$				5.0	V
Reverse Breakdown Voltage	$V_{BR}$	$I_T=1mA$	5.5			V
Reverse Leakage Current	$I_R$	$V_{RWM}=5V, T=25^\circ C$			1	uA
Clamping Voltage	$V_C$	$I_{PP}=8A, t_p=8/20\mu s$		8		V
Junction Capacitance	$C_j$	$V_R = 0V, f = 1MHz$		17		pF

**Electrical Parameters (TA = 25°C unless otherwise noted)**


Symbol	Parameter
$I_{PP}$	Maximum Reverse Peak Pulse Current
$V_C$	Clamping Voltage @ $I_{PP}$
$V_{RWM}$	Working Peak Reverse Voltage
$I_R$	Maximum Reverse Leakage Current @ $V_{RWM}$
$V_{BR}$	Breakdown Voltage @ $I_T$
$I_T$	Test Current




Note:.. 8/20μs pulse waveform.

## Typical Characteristics


**Figure 1: Peak Pulse Power vs. Pulse Time**




**Figure 2: Power Derating Curve**




**Figure 3: Pulse Waveform**



**Figure 4: Clamping Voltage vs.Ipp**



## Outline Drawing – DFN1006



SYMBOL	MILLIMETER		
	MIN	NOM	MAX
<b>A</b>	0.45	0.50	0.55
<b>A1</b>	0	0.02	0.05
<b>b</b>	0.45	0.50	0.55
<b>c</b>	0.12	0.15	0.18
<b>D</b>	0.95	1.00	1.05
<b>e</b>	0.65BSC		
<b>E</b>	0.55	0.60	0.65
<b>L</b>	0.20	0.25	0.30
<b>L1</b>	0.05REF		
<b>h</b>	0.07	0.12	0.17
载体尺寸 (Mill.)	20*20		

## Marking



## Ordering information

Order code	Package	Base qty	Delivery mode
ESDN2L1006C5V01V-B	DFN1006	10K	Tape and reel