


FEATURES


- Epoxy meets UL-94 V-0 flammability rating
- Power dissipation of 300mW
- High stability and high reliability

SOT-23



MECHANICAL DATA

- Case: SOT-23(TO-236)
- Terminals: Plated solderable per MIL-STD-750, method 2026
- Mounting Position: Any
- Marking: 2X



MAXIMUM RATINGS($T_A=25^{\circ}\text{C}$ Unless otherwise specified)

Parameter	Symbol	Unit	Value
Collector-Emitter Voltage	V_{CEO}	V	40
Collector-Base Voltage	V_{CBO}	V	60
Emitter-Base Voltage	V_{EBO}	V	6
Collector Current, Continuous	I_C	mA	600
Collector Power Dissipation	P_D	mW	300
Operation Junction Temperature	T_J	$^{\circ}\text{C}$	-55 to +150
Storage Temperature	T_{STG}	$^{\circ}\text{C}$	-55 to +150
Thermal resistance From junction to ambient	$R_{\theta JA}$	$^{\circ}\text{C}/\text{W}$	417

MMBT4401







ELECTRICAL CHARACTERISTICS(T_A=25°C Unless otherwise specified)

Parameter	Symbol	Unit	Conditions	Min	Max
Collector-Emitter Breakdown Voltage	V _{(BR)CEO}	V	I _C =1.0mA, I _B =0	40	---
Collector-Base Breakdown Voltage	V _{(BR)CBO}	V	I _C =100μA, I _E =0	60	---
Emitter-Base Breakdown Voltage	V _{(BR)EBO}	V	I _E =100μA, I _C =0	6	---
Collector cut-off Current	I _{CBO}	nA	V _{CB} =50V, I _E =0	---	100
Collector cut-off Current	I _{CEO}	nA	V _{CE} =20V, I _B =0	---	---
Emitter cut-off Current	I _{EBO}	nA	V _{EB} =5V, I _C =0	---	100
DC Current Gain	h _{FE(1)}		I _C =0.1mA, V _{CE} =1V	20	---
	h _{FE(2)}		I _C =1mA, V _{CE} =1V	40	---
	h _{FE(3)}		I _C =10mA, V _{CE} =1V	80	---
	h _{FE(4)}		I _C =150mA, V _{CE} =1V	100	300
	h _{FE(5)}		I _C =500mA, V _{CE} =1V	40	---
Collector-Emitter Saturation Voltage	V _{CE(sat)}	V	I _C =150mA, I _B =15mA	---	0.40
			I _C =500mA, I _B =50mA	---	0.75
Base-Emitter Saturation Voltage	V _{BE(sat)}	V	I _C =150mA, I _B =15mA	---	0.95
			I _C =500mA, I _B =50mA	---	1.20
Output Capacitance	C _{ob}	pF	V _{CB} =6V, f=1.0MHz, I _E =0	---	---
Input Capacitance	C _{ib}	pF	V _{EB} =0.5V, f=1.0MHz, I _C =0	---	---
Current Gain-Bandwidth Product	f _T	MHz	I _C =20mA, V _{CE} =10V f=100MHz	250	---
Delay time	t _d	nS	V _{CC} =30V, V _{BE(off)} =-2V I _C =150mA, I _{B1} =15mA	---	15
Rise time	t _r			---	20
Storage time	t _s	nS	V _{CC} =30V, I _C =150mA, I _{B1} =I _{B2} =15mA	---	225
Fall time	t _f			---	60

AVAILABLE PACK INFORMATION


Product code	Pack	Reel Size (mm)	Quantity (Pcs/reel)	Quantity (pcs/box)	Quantity (pcs/carton)
MMBT4401	T/R	Φ180	3K	30K	120K

Characteristics(Typical)




MMBT4401

Outline Dimensions



Dimensions in inches and (millimeters)

Suggested pad layout



Dimensions in millimeters

Friendship Reminder

■ JiNan JingHeng (hereinafter referred to as JH) reserves the right to make changes to this document and its products and specifications at anytime without notice.

■ Customers should obtain and confirm the latest product information and specifications before final design, purchase or use.

■ JH makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does JH assume any liability for application assistance or customer product design.

■ JH does not warrant or accept any liability with products which are purchased or used for any unintended or unauthorized application.

■ No license is granted by implication or otherwise under any intellectual property rights of JH.

■ JH is products are not authorized for use as critical components in life support devices or systems without express written approval of JH.