

General Description

These N-channel enhancement mode power mosfets Used advanced split gate technology design, provided excellent Rds(on) and low gate charge. Which accords with the RoHS standard.

| Product Summary | | | |
|-----------------|------------------------------|--------------------|----------------------|
| V _{DS} | R _{DS(on)} (mΩ) Typ | I _D (A) | Q _g (Typ) |
| 68V | 2.6 @ 10V | 180 | 67nc |

Features

- Fast switching
- Low on-resistance
- Low gate charge and input capacitance
- 100% avalanche tested

Mechanical Data


- Case:TO-220,ITO-220,TO-263,TO-262 Package

Application

- Switching applications

Ordering Information

| Part No. | Package Type | Package | Quality(box) |
|----------|--------------|-------------|--------------|
| D180N06 | TO-220 | Tube | 1000 |
| D180N06F | ITO-220 | Tube | 1000 |
| D180N06D | TO-263 | Tape & Reel | 800 |
| D180N06E | TO-262 | Tube | 1000 |



Block Diagram

Pin Definition:

1. Gate
2. Drain
3. Source




Table1 Absolute Maximum Ratings (T_C=25°C, unless otherwise specified)

| Parameter | Symbol | D180N06/D180N06D/ D180N06E | D180N06F | Unit |
|--|----------------------------------|-------------------------------|----------|------|
| Drain-Source Voltage | V _{DS} | 68 | | V |
| Gate-Source Voltage | V _{GS} | ±20 | | V |
| Continuous Drain Current | I _D | T _C =25°C | 180 | A |
| | | T _C =100°C | 126 | |
| Pulsed Drain Current (Note 1) | I _{DM} | 720 | | A |
| Single Pulse Avalanche Energy(Note 2) | E _{AS} | 1220 | | mJ |
| Avalanche Current(Note 2) | I _{AS} | 70 | | A |
| Power Dissipation T _C =25°C | P _D | 220 | 54 | W |
| Operating Junction and Storage Temperature | T _J /T _{STG} | -55~+175 | | °C |

Table 2. Thermal Characteristics

| Parameter | Symbol | D180N06/D180N06D/ D180N06E | D180N06F | Unit |
|--|-----------------|-------------------------------|----------|-----------------------------|
| Thermal resistance Junction to Ambient | $R_{\theta JA}$ | 75 | 75 | $^{\circ}\text{C}/\text{W}$ |
| Thermal resistance Junction to Case | $R_{\theta JC}$ | 0.68 | 2.78 | $^{\circ}\text{C}/\text{W}$ |

Table 3. Electrical Characteristics ($T_J=25^{\circ}\text{C}$, unless otherwise specified)

| Parameter | Symbol | Test Conditions | Min | Typ | Max | Unit |
|--|--------------|--|-----|------|------|---------------|
| Off Characteristics | | | | | | |
| Drain-Source Breakdown Voltage | BV_{DSS} | $V_{GS}=0V, I_D=250\mu\text{A}$ | 68 | 75 | - | V |
| Drain-Source Leakage Current | I_{DSS} | $V_{DS}=68V, V_{GS}=0V$ | - | - | 1 | μA |
| Gate- Source Leakage Current | Forward | $V_{GS}=20V, V_{DS}=0V$ | - | - | 100 | nA |
| | Reverse | $V_{GS}=-20V, V_{DS}=0V$ | - | - | -100 | nA |
| On Characteristics(Note 3) | | | | | | |
| Gate Threshold Voltage | $V_{GS(TH)}$ | $V_{DS}=V_{GS}, I_D=250\mu\text{A}$ | 2.0 | 3.0 | 4.0 | V |
| Static Drain-Source On-State Resistance | $R_{DS(ON)}$ | $V_{GS}=10V, I_D=75A$ | - | 2.6 | 3.3 | m Ω |
| Dynamic Characteristics | | | | | | |
| Input Capacitance | C_{ISS} | $V_{DS}=35V, V_{GS}=0V, f=1\text{MHz}$ | - | 4439 | - | pF |
| Output Capacitance | C_{OSS} | | - | 1624 | - | pF |
| Reverse Transfer Capacitance | C_{RSS} | | - | 65 | - | pF |
| Switching Characteristics | | | | | | |
| Turn-On Delay Time | $t_{d(on)}$ | $V_{DD}=35V, I_D=75A$ $V_{GS}=10V, R_G=2.0\Omega$ | - | 19 | - | ns |
| Turn-On Rise Time | t_R | | - | 100 | - | ns |
| Turn-Off Delay Time | $t_{d(off)}$ | | - | 38 | - | ns |
| Turn-Off Fall Time | t_f | | - | 107 | - | ns |
| Total Gate Charge | Q_G | $V_{DD}=35V, I_D=75A,$ $V_{GS}=10V$ | - | 67 | - | nC |
| Gate-Source Charge | Q_{GS} | | - | 27 | - | nC |
| Gate-Drain Charge | Q_{GD} | | - | 12 | - | nC |
| Drain-Source Diode Characteristics and Maximum Ratings(Note 3) | | | | | | |
| Drain-Source Diode Forward Voltage | V_{SD} | $V_{GS}=0V, I_S=90A$ | - | - | 1.3 | V |
| Maximum Continuous Drain-Source Diode Forward Current | I_S | | - | - | 180 | A |
| Reverse Recovery Time | t_{rr} | $V_{GS}=0V, I_F=75A$ $dI_F/dt=100A/\mu\text{s}$ | - | 62 | - | ns |
| Reverse Recovery Charge | Q_{RR} | | - | 68 | - | nC |

Notes : 1 Repetitive Rating: Pulse width limited by maximum junction temperature

2 $L=0.5\text{mH}, I_D=70A, V_{DD}=50V, \text{Starting } T_J=25^{\circ}\text{C}$

3 Pulse Test: Pulse width $\leq 300\mu\text{s}$, Duty cycle $\leq 2\%$

Typical Characteristics Diagrams




Figure 1 Output Characteristics




Figure 2 Transfer Characteristics




Figure 3. Threshold vs Temperature




Figure 4. $R_{ds(on)}$ vs Temperature

Typical Characteristics Diagrams




Figure 5. Power De-rating




Figure 6. ID Current Derating




Figure 7. Capacitance Characteristics






Figure 8. Gate Charge Characteristics


Typical Test Circuit




1) Gate Charge Test Circuit



2) Gate Charge Waveform




3) Resistive Switching Test Circuit




4) Resistive Switching Waveforms


Typical Test Circuit




5) Diode Reverse Recovery Test Circuit



6) Diode Reverse Recovery Waveform




7) . Unclamped Inductive Switching Test Circuit




8) Unclamped Inductive Switching Waveforms

Product Names Rules




Dimensions

TO-220 PACKAGE OUTLINE DIMENSIONS



| Symbol | Dimensions In Millimeters | | Dimensions In Inches | |
|--------|---------------------------|-------|----------------------|-------|
| | MIN | MAX | MIN | MAX |
| A | 4.25 | 4.87 | 0.167 | 0.192 |
| A1 | 1.07 | 1.47 | 0.042 | 0.058 |
| A2 | 2.03 | 2.92 | 0.080 | 0.115 |
| b | 0.51 | 1.11 | 0.020 | 0.044 |
| b1 | 0.97 | 1.6 | 0.038 | 0.063 |
| C | 0.3 | 0.7 | 0.012 | 0.028 |
| D | 14.6 | 15.9 | 0.575 | 0.626 |
| D1 | 8.04 | 9.3 | 0.317 | 0.366 |
| E | 9.57 | 10.57 | 0.377 | 0.416 |
| e | 2.34 | 2.74 | 0.092 | 0.108 |
| L | 12.58 | 14.3 | 0.495 | 0.563 |
| L1 | 2.8 | 4.2 | 0.110 | 0.165 |
| P | 3.4 | 4.14 | 0.134 | 0.163 |
| Q | 2.45 | 3 | 0.096 | 0.118 |


ITO-220 PACKAGE OUTLINE DIMENSIONS



| Symbol | Dimensions In Millimeters | | Dimensions In Inches | |
|--------|---------------------------|-------|----------------------|-------|
| | MIN | MAX | MIN | MAX |
| A | 4.24 | 4.9 | 0.167 | 0.193 |
| A1 | 2.3 | 2.92 | 0.091 | 0.115 |
| A2 | 2.61 | 2.81 | 0.103 | 0.111 |
| b | 0.3 | 1 | 0.012 | 0.039 |
| b1 | 0.9 | 1.55 | 0.035 | 0.061 |
| C | 0.3 | 0.7 | 0.012 | 0.028 |
| D | 14.5 | 16.36 | 0.571 | 0.644 |
| D1 | 8.8 | 9.41 | 0.346 | 0.370 |
| E | 9.5 | 10.5 | 0.374 | 0.413 |
| e | 2.3 | 2.75 | 0.091 | 0.108 |
| L | 12.6 | 14 | 0.496 | 0.551 |
| L1 | 2.45 | 4.3 | 0.096 | 0.169 |
| P | 2.9 | 3.8 | 0.114 | 0.150 |
| Q | 2.5 | 3.55 | 0.098 | 0.140 |


Dimensions

TO-263 PACKAGE OUTLINE DIMENSIONS



| Symbol | Dimensions In Millimeters | | Dimensions In Inches | |
|--------|---------------------------|-------|----------------------|-------|
| | MIN | MAX | MIN | MAX |
| A | 4.25 | 4.87 | 0.167 | 0.192 |
| A1 | 1.07 | 1.47 | 0.042 | 0.058 |
| A2 | 0 | 0.25 | 0.000 | 0.010 |
| b | 0.61 | 1.01 | 0.024 | 0.040 |
| b1 | 1.2 | 1.34 | 0.047 | 0.053 |
| C | 0.3 | 0.6 | 0.012 | 0.024 |
| D | 9.48 | 10.84 | 0.373 | 0.427 |
| D1 | 8.49 | 9.3 | 0.334 | 0.366 |
| E | 9.7 | 10.31 | 0.382 | 0.406 |
| e | 4.88 | 5.28 | 0.192 | 0.208 |
| L | 4.46 | 5.85 | 0.176 | 0.230 |
| L1 | 1.33 | 2.33 | 0.052 | 0.092 |
| L2 | 0 | 2.2 | 0.000 | 0.087 |

TO-262 PACKAGE OUTLINE DIMENSIONS



| Symbol | Dimensions In Millimeters | | Dimensions In Inches | |
|--------|---------------------------|-------|----------------------|-------|
| | MIN | MAX | MIN | MAX |
| A | 10.14 | 11.14 | 0.399 | 0.439 |
| B | 9.57 | 10.57 | 0.377 | 0.416 |
| C | 1.15 | 1.84 | 0.045 | 0.072 |
| D | 2.95 | 3.95 | 0.116 | 0.156 |
| E | 12.25 | 13.75 | 0.482 | 0.541 |
| F | 2.34 | 2.74 | 0.092 | 0.108 |
| G | 0.51 | 1.11 | 0.020 | 0.044 |
| H | 0.97 | 1.57 | 0.038 | 0.062 |
| I | 4.25 | 4.87 | 0.167 | 0.192 |
| J | 1.07 | 1.47 | 0.042 | 0.058 |
| K | 2.03 | 2.92 | 0.080 | 0.115 |
| L | 0.3 | 0.6 | 0.012 | 0.024 |

Friendship Reminder

┌ JiNan JingHeng hereinafter referred to as JH reserves the right to make changes to this document and its products and specifications at anytime without notice.

┌ Customers should obtain and confirm the latest product information and specifications before final design, purchase or use.

┌ JH makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does JH assume any liability for application assistance or customer product design.

┌ JH does not warrant or accept any liability with products which are purchased or used for any unintended or unauthorized application.

┌ No license is granted by implication or otherwise under any intellectual property rights of JH.

┌ JH's products are not authorized for use as critical components in life support devices or systems without express written approval of JH.