



Features

- Plastic package has Underwriters Laboratory Flammability Classification 94V-0
- Ultrafast and soft recovery time for high efficiency
- Low VF ,Low power loss
- Polyimide passivation
- Very short recovery time and low I_{rrm}
- Soft recovery behaviour for low EMI/RFI
- High surge capability
- High temperature soldering guaranteed:260°C/10 seconds at terminals
- Component in accordance to RoHS 2015/863/EU

TO-263(D²PAK)



Mechanical Data

- Case: JEDEC TO-263(D²PAK) molded plastic body
- Terminals: Lead solderable per MIL-STD-750,method 2026
- Polarity: As marked
- Mounting Position: Any

Typical Applications

For use in boost stage in SMPS
high frequency inverters for solar inverters
DC/DC converters
high frequency output rectification of battery chargers
free wheeling diodes in motor drivers

PRIMARY CHARACTERISTICS	
I _{F(AV)}	60.0A
V _R	300V
I _{FSM}	550A
V _F at I _F =60.0A,25°C	1.25V
T _{rr typ}	40ns
T _{JMAX}	175°C

Maximum Ratings

(Ratings at 25°C ambient temperature unless otherwise specified)

Parameter	Symbol	Value	Unit
Maximum repetitive peak reverse voltage	V _{RRM}	300	V
Maximum average forward rectified current, Rectangular wave, D=0.5, T _c =135°C	I _{F(AV)}	60	A
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load (JEDEC method at rated T _J)	I _{FSM}	550	A
Operating junction temperature range	T _J	-55 to+175	°C
Storage temperature range	T _{STG}	-55 to+175	°C

Electrical Characteristics (T_J=25°C Unless otherwise noted)

Parameter	Test Conditions		Symbol	Min.	Typ.	Max.	Unit
Breakdown voltage Blocking voltage	I _R =200μA		V _{BR} V _R	300	-	-	V
Instaneous forward voltage	T _J =25°C	I _F =60A	V _F ¹⁾	-	1.25	1.43	V
		I _F =120A		-	-	1.78	
	T _J =150°C	I _F =60A		-	-	1.14	
		I _F =120A		-	-	1.53	
Reverse current	T _J =25°C	V _R =300V	I _R ²⁾	-	-	1	μA
	T _J =150°C			-	-	350	
Junction capacitance	4V,1MHz		C _J	-	260	-	pF

Notes: 1.Pulse test: 300 μs pulse width,1% duty cycle

2.Pulse test: pulse width≤40ms

Dynamic Recovery Characteristics (T_J=25°C Unless otherwise noted)

Parameter	Test Conditions		Symbol	Min.	Typ.	Max.	Unit
Reverse recovery time	I _F =0.5A,I _R =1.0A, I _{rr} =0.25A		trr	-	40	55	ns
	T _J =25°C	I _F =60A dI _F /dt=200A/μS V _R =200V		-	35	-	
	T _J =125°C			-	65	-	
Peak recovery current	T _J =25°C	I _F =60A dI _F /dt=200A/μS V _R =200V	I _{RRM}	-	3.5	-	A
	T _J =125°C			-	9.1	-	
Reverse recovery charge	T _J =25°C	I _F =60A dI _F /dt=200A/μS V _R =200V	Q _{rr}	-	86	-	nC
	T _J =125°C			-	320	-	

Thermal Characteristics


Parameter	Symbol	TO-263	Unit
Typical thermal resistance ³⁾	$R_{\theta jc}$	0.45	$^{\circ}\text{C}/\text{W}$

3. Thermal resistance from junction to case

Available Pack Information

Product code	Pack	Box Size L×W×H(mm)	Quantity(pcs/box)	Carton SizeL×W×H(mm)	Quantity(box/carton)
MURS6030D3-TO-263	P/T	558×148×38	1000	565×225×170	5

Equivalent circuits for power loss calculation



V_{F0} : threshold voltage 0.69V

r_d : Dynamic resistance 0.0064 Ω

Forward power loss of diode = $V_{F0} \times I_{F(AV)} + r_d \times I_{F(RMS)}^2$

FIG.1-FORWARD CURRENT DERATING CURVE




FIG.2-MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




Fig.3-typical Instantaneous Forward Characteristics







Fig.4-Typical Reverse Characteristics



TO-263



Suggested Pad Layout



Dimensions in inches and (millimeters)

Friendship Reminder

- JiNan JingHeng (hereinafter referred to as JH) reserves the right to make changes to this document and its products and specifications at anytime without notice.

- Customers should obtain and confirm the latest product information and specifications before final design, purchase or use.

- JH makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does JH assume any liability for application assistance or customer product design.

- JH does not warrant or accept any liability with products which are purchased or used for any unintended or unauthorized application.

- No license is granted by implication or otherwise under any intellectual property rights of JH.

- JH's products are not authorized for use as critical components in life support devices or systems without express written approval of JH.