

## FEATURES

- $R_{DS(ON)} < 0.17\Omega @ V_{GS} = 10V$
- 100% avalanche tested
- RoHS compliant

## MECHANICAL DATA


- Case: TO-220, ITO-220, TO-263, TO-247 package

## Ordering Information

Part No.	Package Type	Package	Quality(box)
SJ22N65	TO-220	Tube	1000
SJ22N65F	ITO-220	Tube	1000
SJ22N65D	TO-263	Tape & Reel	800
SJ22N65P	TO-247	Tube	360

## PRODUCT SUMMARY

$V_{DS}(V)$	$R_{DS(on)}(\Omega)_{Typ}$	$I_D(A)$
650	0.15@ $V_{GS} = 10V$	22



## Block Diagram

Pin Definition:

1. Gate
2. Drain
3. Source




Table1 Absolute Maximum Ratings ( $T_C = 25^\circ C$ , unless otherwise specified)

Parameter	Symbol	TO-220/TO-263/TO-247	ITO-220	Unit
Drain-Source Voltage	$V_{DS}$	650		V
Gate-Source Voltage	$V_{GS}$	$\pm 30$		V
Continuous Drain Current	$I_D$	$T_C = 25^\circ C$	22 *	A
		$T_C = 100^\circ C$	13 *	
Pulsed Drain Current (Note 1)	$I_{DM}$	48		A
Single Pulse Avalanche Energy(Note 2)	$E_{AS}$	485		mJ
Avalanche Current(Note 1)	$I_{AR}$	3.5		A
Repetitive Avalanche Energy(Note 1)	$E_{AR}$	1		mJ
Peak Diode Recovery $dv/dt$ (Note 3)	$dv/dt$	15		V/ns
Drain Source voltage slope( $V_{ds} = 480V$ )	$dV_{ds}/dt$	50		V/ns
Power Dissipation $T_C = 25^\circ C$	$P_D$	151	35	W
Operating Junction and Storage Temperature	$T_J/T_{STG}$	-55 ~ +150		$^\circ C$
Maximum Temperature for soldering	$T_L$	300		$^\circ C$

※ limited by maximum junction temperature

## SJ22N65 Series

Table 2. Thermal Characteristics

Parameter	Symbol	TO-220/TO-263/TO-247	ITO-220	Unit
Thermal resistance Junction to Ambient	$R_{\theta JA}$	62	62	$^{\circ}\text{C/W}$
Thermal resistance Junction to Case	$R_{\theta JC}$	0.82	3.57	$^{\circ}\text{C/W}$

Table 3. Electrical Characteristics ( $T_J=25^{\circ}\text{C}$ , unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Off Characteristics						
Drain-Source Breakdown Voltage	$BV_{DSS}$	$V_{GS}=0V, I_D=250\mu\text{A}$	650	--	--	V
Drain-Source Leakage Current	$I_{DSS}$	$V_{DS}=650V, V_{GS}=0V$	--	--	1	$\mu\text{A}$
Gate- Source Leakage Current	Forward	$V_{GS}=30V, V_{DS}=0V$	--	--	100	nA
	Reverse	$V_{GS}=-30V, V_{DS}=0V$	--	--	-100	nA
On Characteristics(Note 4)						
Gate Threshold Voltage	$V_{GS(TH)}$	$V_{DS}=V_{GS}, I_D=250\mu\text{A}$	2	--	4	V
Static Drain-Source On-State Resistance	$R_{DS(ON)}$	$V_{GS}=10V, I_D=11A$	--	0.15	0.17	$\Omega$
Dynamic Characteristics(Note 5)						
Input Capacitance	$C_{ISS}$	$V_{DS}=25V, V_{GS}=0V, f=1\text{MHz}$	--	1510	--	pF
Output Capacitance	$C_{OSS}$		--	75	--	pF
Reverse Transfer Capacitance	$C_{RSS}$		--	6	--	pF
Switching Characteristics (Note 5)						
Turn-On Delay Time	$t_d(\text{on})$	$V_{DD}=520V, I_D=11A,$ $R_G=20\Omega$	--	25	--	ns
Turn-On Rise Time	$t_R$		--	17	--	ns
Turn-Off Delay Time	$t_d(\text{off})$		--	130	--	ns
Turn-Off Fall Time	$t_f$		--	11	--	ns
Total Gate Charge	$Q_G$	$V_{DS}=520V, I_D=11A,$ $V_{GS}=10V$	--	38	--	nC
Gate-Source Charge	$Q_{GS}$		--	8.5	--	nC
Gate-Drain Charge	$Q_{GD}$		--	13	--	nC
Drain-Source Diode Characteristics and Maximum Ratings						
Drain-Source Diode Forward Voltage	$V_{SD}$	$V_{GS}=0V, I_S=11A$	--	0.9	1.5	V
Maximum Continuous Drain-Source Diode Forward Current	$I_S$		--	--	22	A
Reverse Recovery Time	$t_{rr}$	$V_{GS}=0V, I_F=11A$	--	475	--	ns
Reverse Recovery Charge	$Q_{RR}$	$di/dt=100A/\mu\text{s}$ (Note 1)	--	5800	--	nC

Notes : 1 Repetitive Rating: Pulse width limited by maximum junction temperature

2  $L=60\text{mH}, I_{AS}=3A, V_{DD}=150V$ , Starting  $T_J=25^{\circ}\text{C}$


3  $I_{SD}\leq 4.5A, di/dt\leq 200A/\mu\text{s}, V_{DD}\leq BV_{DSS}$ , Starting  $T_J=25^{\circ}\text{C}$

4 Pulse Test: Pulse width  $\leq 300\mu\text{s}$ , Duty cycle  $\leq 2\%$

5 Guaranteed by design, not subject to production


Typical characteristics Diagrams

**Power dissipation**  
TO-220,TO-263,TO-247




$P_{tot} = f(T_c)$

**Power dissipation**  
ITO-220




$P_{tot} = f(T_c)$

**Max. transient thermal impedance**  
TO-220,TO-263,TO-247



$Z_{(thJC)} = f(t_p)$ ; parameter:  $D = t_p / T$

**Max. transient thermal impedance**  
ITO-220




$Z_{(thJC)} = f(t_p)$ ; parameter:  $D = t_p / T$

# SJ22N65 Series


## Typical characteristics Diagrams

Safe operating area  $T_C=25\text{ }^\circ\text{C}$   
TO-220, TO-263, TO-247




$I_D=f(V_{DS}); T_C=25\text{ }^\circ\text{C}; D=0$ ; parameter  $t_p$

Safe operating area  $T_C=25\text{ }^\circ\text{C}$   
ITO-220




$I_D=f(V_{DS}); T_C=25\text{ }^\circ\text{C}; D=0$ ; parameter  $t_p$

Typ. output characteristics  $T_C=25\text{ }^\circ\text{C}$



$I_D=f(V_{DS}); T_j=25\text{ }^\circ\text{C}$ ; parameter:  $V_{GS}$



Typ. output characteristics  $T_j=125\text{ }^\circ\text{C}$



$I_D=f(V_{DS}); T_j=125\text{ }^\circ\text{C}$ ; parameter:  $V_{GS}$


# SJ22N65 Series

## Typical characteristics Diagrams



# SJ22N65 Series

## Typical characteristics Diagrams



TYPICAL TEST CIRCUIT

Table 20 Switching times test circuit and waveform for inductive load




Table 21 Unclamped inductive load test circuit and waveform






Table 22 Test circuit and waveform for diode characteristics



Product Names Rules






# SJ22N65 Series


## Dimensions

### TO-220 PACKAGE OUTLINE DIMENSIONS



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	MIN	MAX	MIN	MAX
A	4.25	4.87	0.167	0.192
A1	1.07	1.47	0.042	0.058
A2	2.03	2.92	0.080	0.115
b	0.51	1.11	0.020	0.044
b1	0.97	1.6	0.038	0.063
C	0.3	0.7	0.012	0.028
D	14.6	15.9	0.575	0.626
D1	8.04	9.3	0.317	0.366
E	9.57	10.57	0.377	0.416
e	2.34	2.74	0.092	0.108
L	12.58	14.3	0.495	0.563
L1	2.8	4.2	0.110	0.165
P	3.4	4.14	0.134	0.163
Q	2.45	3	0.096	0.118

### ITO-220 PACKAGE OUTLINE DIMENSIONS




Symbol	Dimensions In Millimeters		Dimensions In Inches	
	MIN	MAX	MIN	MAX
A	4.24	4.9	0.167	0.193
A1	2.3	2.92	0.091	0.115
A2	2.61	2.81	0.103	0.111
b	0.3	1	0.012	0.039
b1	0.9	1.55	0.035	0.061
C	0.3	0.7	0.012	0.028
D	14.5	16.36	0.571	0.644
D1	8.8	9.41	0.346	0.370
E	9.5	10.5	0.374	0.413
e	2.3	2.75	0.091	0.108
L	12.6	14	0.496	0.551
L1	2.45	4.3	0.096	0.169
P	2.9	3.8	0.114	0.150
Q	2.5	3.55	0.098	0.140

# SJ22N65 Series


## Dimensions

### TO-263 PACKAGE OUTLINE DIMENSIONS



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	MIN	MAX	MIN	MAX
A	4.25	4.87	0.167	0.192
A1	1.07	1.47	0.042	0.058
A2	0	0.25	0.000	0.010
b	0.61	1.01	0.024	0.040
b1	1.2	1.34	0.047	0.053
C	0.3	0.6	0.012	0.024
D	9.48	10.84	0.373	0.427
D1	8.49	9.3	0.334	0.366
E	9.7	10.31	0.382	0.406
e	4.88	5.28	0.192	0.208
L	4.46	5.85	0.176	0.230
L1	1.33	2.33	0.052	0.092
L2	0	2.2	0.000	0.087

### TO-247 PACKAGE OUTLINE DIMENSIONS



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	min.	max.	min.	max.
A	4.90	5.10	0.193	0.201
A1	2.31	2.51	0.091	0.099
A2	1.90	2.10	0.075	0.083
b	1.16	1.26	0.046	0.050
b1	1.96	2.06	0.0772	0.0812
b2	2.96	3.06	0.117	0.121
c	0.59	0.66	0.0232	0.0260
D	20.90	21.10	0.8235	0.8313
D1	16.25	16.85	0.6403	0.6639
E	15.70	15.90	0.6186	0.6265
E1	13.10	13.50	0.5161	0.5319
e	5.44		0.2143	
L	19.80	20.10	0.7801	0.7919
ΦP	3.50	3.70	0.1379	0.1458
ΦP1	0	7.30	0	0.2876

## Friendship Reminder

■ JiNan JingHeng ( hereinafter referred to as JH ) reserves the right to make changes to this document and its products and specifications at anytime without notice.

■ Customers should obtain and confirm the latest product information and specifications before final design, purchase or use.

■ JH makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does JH assume any liability for application assistance or customer product design.

■ JH does not warrant or accept any liability with products which are purchased or used for any unintended or unauthorized application.

■ No license is granted by implication or otherwise under any intellectual property rights of JH.

■ JH's products are not authorized for use as critical components in life support devices or systems without express written approval of JH.