

Features


- High blocking voltage with low on-resistance
- High speed switching with low capacitance
- High operating junction temperature capability
- Very fast and robust intrinsic body diode
- Kelvin gate input easing driver circuit design

Product Summary			
V _{DS}	R _{DS(on)} (mΩ)Typ	I _D (A)	Q _g (Typ)
1200V	7 @ 18V 100A	240	515nc

SOT-227

Mechanical Data

- Case:SOT-227 Package



Application

- Motor drivers
- Solar inverters
- Automotive DC/DC converters
- Automotive compressor inverters
- Switch mode power supplies

Block Diagram




Table1 Absolute Maximum Ratings (T_C=25°C, unless otherwise specified)

Parameter	Symbol	Value	Unit
Drain-Source Voltage	V _{DS}	1200	V
Gate-Source Voltage(Max)	V _{GS(DC)}	-8/+22	V
Gate-Source Voltage	V _{GS(OP)}	-4/+18	V
Continuous Drain Current	I _D	T _C =25°C	240
		T _C =100°C	170
Pulsed Drain Current (Note 1)	I _{DM}	960	A
Power Dissipation T _C =25°C	P _D	750	W
Operating Junction and Storage Temperature	T _J /T _{STG}	-55 ~ +175	°C

Table 2.Thermal Characteristics

Parameter	Symbol	SC07N120S7P	Unit
Thermal resistance Junction to Case	R _{θJC}	0.2	°C/W

Table 3. Electrical Characteristics (T_J=25°C, unless otherwise specified)

Parameter		Symbol	Test Conditions	Min	Typ	Max	Unit
Off Characteristics							
Drain-Source Breakdown Voltage		BV _{DSS}	V _{GS} =0V,I _D =100μA	1200	-	-	V
Drain-Source Leakage Current		I _{DSS}	V _{Ds} =1200V,V _{GS} =0V	-	-	100	μA
Gate- Source Leakage Current	Forward	I _{GSS}	V _{GS} =22V,V _{Ds} =0V	-	-	250	nA
	Reverse		V _{GS} =-8V,V _{Ds} =0V	-	-	-250	nA
On Characteristics							
Gate Threshold Voltage		V _{GS(TH)}	V _{Ds} =V _{GS} ,I _D =45mA	2.0	2.4	3.0	V
Static Drain-Source On-State Resistance		R _{DS(ON)}	V _{GS} =18V,I _D =100A,T _J =25°C	-	7	10	mΩ
			V _{GS} =18V,I _D =100A,T _J =175°C	-	12	-	
Gate Resisitance		R _G	f=1MHz	-	1.9	-	Ω
Dynamic Characteristics							
Input Capacitance		C _{ISS}	V _{Ds} =1000V,V _{GS} =0V, f=1MHz,V _{AC} =25mV	-	11500	-	pF
Output Capacitance		C _{OSS}		-	563	-	pF
Reverse Transfer Capacitance		C _{RSS}		-	37	-	pF
Coss stored energy		E _{OSS}		-	315	-	μJ
Turn-on switching energy		E _{ON}	V _{Ds} =800V,I _D =100A V _{GS} =-4/18V,R _G =3Ω, L=100μH,T _J =25°C	-	2059	-	μJ
Turn-off switching energy		E _{OFF}		-	1185	-	μJ
Turn-On Delay Time		td(on)		-	33	-	ns
Turn-On Rise Time		t _R		-	41	-	ns
Turn-Off Delay Time		td(off)		-	96	-	ns
Turn-Off Fall Time		t _f		-	23	-	ns
Total Gate Charge		Q _G	V _{DD} =800V,I _D =100A, V _{GS} =-4/18V	-	515	-	nC
Gate-Source Charge		Q _{GS}		-	207	-	nC
Gate-Drain Charge		Q _{GD}		-	30	-	nC
Drain-Source Diode Characteristics and Maximum Ratings(Note 2)							
Drain-Source Diode Forward Voltage		V _{SD}	V _{GS} =0V,I _S =100A	-	4.1	-	V
Reverse Recovery Time		trr	V _{GS} =-4V, V _R =800V, I _{SD} =100A,diF/dt=3000A/μs	-	29	-	ns
Recovered charge		Q _{rr}		-	839	-	nC
Peak reverse recovery current		I _{rrm}		-	51	-	A

Notes: 1 RepetitiveRating Pulse width limited by maximum junction temperature

2 Pulse Test: Pulse width ≤300μs, Duty cycle≤2%

Typical Characteristics Diagrams




Figure 1. Output Characteristics $T_J = -55\text{ }^{\circ}\text{C}$




Figure 2. Output Characteristics $T_J = 25\text{ }^{\circ}\text{C}$




Figure 3. Output Characteristics $T_J = 175\text{ }^{\circ}\text{C}$




Figure 4. Normalized On-Resistance vs. Temperature




Figure 5. On-Resistance vs. Drain Current for Various Temperatures




Figure 6. On-Resistance vs. Temperature for Various Gate Voltages

Typical Characteristics Diagrams




Figure 7. Transfer Characteristics for Various Junction Temperatures




Figure 8. Body Diode Characteristics at -55°C




Figure 9. Body Diode Characteristics at 25°C




Figure 10. Body Diode Characteristics at 175°C




Figure 11. Threshold Voltage vs. Temperature




Figure 12. Gate Charge Characteristics

Typical Characteristics Diagrams




Figure 13. 3rd Quadrant Characteristics at -55 °C




Figure 14. 3rd Quadrant Characteristics at 25 °C




Figure 15. 3rd Quadrant Characteristics at 175 °C




Figure 16. Output Capacitor Stored Energy




Figure 17. Capacitances vs. Drain-Source Voltage (0 - 200V)




Figure 18. Capacitances vs. Drain-Source Voltage (0 - 1000V)

Typical Characteristics Diagrams




Figure 19. Transient Thermal Impedance (Junction - Case)




Figure 20. Safe Operating Area




Figure 21. Switching Losses vs. $R_{G(ext)}$




Figure 22. Switching Times vs. $R_{G(ext)}$




Figure 23. Switching Losses vs. Temperature




Figure 24. Switching Losses vs. Drain Current

Typical Characteristics Diagrams




Figure 25. Continuous Drain Current Derating vs. Case Temperature





Figure 26. Maximum Power Dissipation Derating vs. Case Temperature

Dimensions

SOT-227packag



SYMBOLS	DIMENSION IN MM		
	MIN	NOM	MAX
<i>A</i>	31.20	31.70	32.20
<i>B</i>	7.50	8.00	8.50
<i>C</i>	3.80	4.20	4.60
<i>D</i>	3.80	4.20	4.60
<i>E</i>	3.80	4.20	4.60
<i>F</i>	14.50	15.00	15.50
<i>G</i>	29.80	30.20	30.60
<i>H</i>	37.70	38.10	38.50
<i>J</i>	11.50	11.90	12.30
<i>K</i>	8.90	9.50	10.00
<i>L</i>	0.75	0.80	0.85
<i>M</i>	12.40	12.70	13.00
<i>N</i>	25.00	25.40	25.80
<i>O</i>	1.70	2.00	2.30
<i>P</i>	4.95	5.60	6.10
<i>Q</i>	26.40	26.70	27.00
<i>R</i>	3.90	4.18	4.45
<i>S</i>	4.20	4.80	5.40
<i>T</i>	23.80	24.80	25.80

Friendship Reminder

■ JiNan JingHeng (hereinafter referred to as JH) reserves the right to make changes to this document and its products and specifications at anytime without notice.

■ Customers should obtain and confirm the latest product information and specifications before final design, purchase or use.

■ JH makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does JH assume any liability for application assistance or customer product design.

■ JH does not warrant or accept any liability with products which are purchased or used for any unintended or unauthorized application.

■ No license is granted by implication or otherwise under any intellectual property rights of JH.

■ JH's products are not authorized for use as critical components in life support devices or systems without express written approval of JH.